



**FEATURES:**

- ✓ Architectural adjustable luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ High efficiency optical system is available with 20° Spot, 40° Flood or 60° wide Flood Beam angle.
- ✓ Integrated TRIAC/ELV dimming driver is placed into sleek minimalistic body of the luminaire.
- ✓ Available in white and black finishes.
- ✓ Comes standard with Juno track adapter.
- ✓ LED spot is rated for 60,000hrs. L70 with +90 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

**SPECIFICATION:**

**SOURCE**

- 
- 10WLED

**RADIANCE**

- 
- DD - Direct (100%Down)
- 
- \*Light Distribution.

**VOLTAGE**

- 
- 120V
- 
- 
- 277V

**DRIVER**

- 
- ST - Standard (Non-Dimming)
- 
- 
- DT - TRIAC

**MOUNTING**

- 
- JT-Juno Track
- 
- 
- 
- \*
- 
- \*Other track adapters are available.

**REFLECTOR**

- 
- SP - Spot
- 
- 
- FL - Flood
- 
- 
- WF - Wide Flood

**FINISH**


- 
- WH - White
- 
- 
- BK - Black
- 
- 
- GR - Grey

**CCT**

- 
- 30K/90CRI - 3000Kelvin
- 
- 
- 35K/90CRI - 3500Kelvin
- 
- 
- 40K/90CRI - 4000Kelvin
- 
- \*Other options are available.

**DIMENSIONS:**

Height	Width	Diameter
5.500"	4.125"	2.375"


**LUMEN OUTPUT:**

Watts	30K	35K	40K
10W	950 lm	1000 lm	1050 lm



Project:

Type: