




FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ Available with white aluminum or optional polycarbonate prismatic reflector.
- ✓ Suitable for suspended installation.
- ✓ Aluminum body with integrated driver.
- ✓ Available in white, black or grey finish.
- ✓ LED spot is rated for 60,000hrs. L70 with +90 CRI.
- ✓ Has a proven record in office and commercial installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SPECIFICATION:



Enter the Product Code into the boxes above.

SOURCE

- 17W LED
- 34W LED

RADIANCE

- DD - Direct (100%Down)
- *Light Distribution.

VOLTAGE

- 120V
- 277V
- 347V*

*Not available for all configurations.

DRIVER

- ST - Standard (Non-Dimming)
- DL - 0-10V Dimming (1%)
- DA - DALI
- BT - Bluetooth
- *

* Please specify dimming method.

MOUNTING

- S4-Suspension 4Feet
- S6-Suspension 6Feet
- S Feet*

*Please specify required Length.

REFLECTOR

- AL - Aluminum
- PR - Prismatic

FINISH

- WH - White
- BK - Black
- GR - Grey


CCT

- 30K/90CRI - 3000Kelvin
- 35K/90CRI - 3500Kelvin
- 40K/90CRI - 4000Kelvin

*Other options are available.

DIMENSIONS:

Height	Width
13.75"	12.25"



LUMEN OUTPUT:

Watts	30K	35K	40K
17W	1950 lm	2000 lm	2050 lm
34W	3900 lm	4000 lm	4100 lm



Project:

Type: